

IN THE CLAIMS:

Please amend Claims 1, 3-6, 9 and 10 as follows.

1. (Currently Amended) An electrophoretic display device, comprising:  
a first substrate and a second substrate which are disposed with a  
spacing therebetween,  
a partition wall disposed in the spacing,  
electrophoretic particles sealed in a closed space, defined by the first  
and second substrates and the partition wall, ~~in which a distribution state of the electrophoretic  
particles is changed to effect display,~~  
a first electrode disposed at a side surface of the closed space, and  
a second electrode disposed at a bottom surface of the closed space,  
with distribution of the electrophoretic particles in the closed space  
being changed according to a voltage between the first and second electrodes to effect display,  
wherein the first electrode has an area substantially equal to or larger  
than an area of the second electrode.
2. (Original) A device according to Claim 1, wherein the area of the first  
electrode is substantially not more than three times the area of the second electrode.

3. (Currently Amended) A device according to Claim 1 ~~or 2~~, wherein the first electrode is disposed at opposite two side surfaces of the closed space.

4. (Currently Amended) A device according to Claim 1 ~~or 2~~, wherein the first electrode is disposed at four side surfaces of the closed space.

5. (Currently Amended) A device according to Claim 1 ~~or 2~~, wherein the first electrode is disposed at opposite two side surfaces of the closed space, and at other opposite two side surfaces of the closed space, a side surface electrode for cancelling an influence of an electric field, on an adjacent pixel, generated by the first and second electrodes is disposed.

6. (Currently Amended) A device according to ~~any one of Claims 1-5~~ Claim 1, wherein each of the first and second electrodes is coated with an insulating layer at a surface thereof.

7. (Original) A device according to Claim 6, wherein the first electrode has an area equal to an area of the second electrode, and a first distance from the first electrode to a surface of an insulating layer disposed on the first electrode is equal to a second distance from the second electrode to a surface of an insulating layer disposed on the second electrode, and  
wherein when an intersection line is taken as a line of intersection of an extended plane of an electrode surface of the first electrode and an extended plane of an electrode

surface of the second electrode, a distance from the intersection line to an edge of the first electrode surface closest to the intersection line is equal to a distance from the intersection line to an edge of the second electrode surface closest to the intersection line.

8. (Original) A device according to Claim 7, wherein the first electrode has an area equal to an area of the second electrode, and

wherein when the first distance and the second distance satisfy the following relationship: (first distance) > (second distance), the following relationship is satisfied: (electrode area of first electrode) < (electrode area of second electrode), and when the first distance and the second distance satisfy the following relationship: (first distance) < (second distance), the following relationship is satisfied: (electrode area of first electrode) > (electrode area of second electrode).

9. (Currently Amended) A device according to ~~any one of Claims 1-7~~ Claim 1, wherein the closed space has a ratio ~~(width) : (length)~~ of width to length of not less than 1:3 at a top surface or a bottom surface thereof.

10. (Currently Amended) An electrophoretic display device, comprising:  
a first substrate and a second substrate which are disposed with a spacing therebetween,  
a partition wall disposed in the spacing,

electrophoretic particles sealed in a closed space, defined by the first and second substrates and the partition wall, ~~in which a distribution state of the electrophoretic particles is changed to effect display,~~

a first electrode disposed at a side surface of the closed space, ~~and~~  
a second electrode disposed at a bottom surface of the closed space,  
distribution of the electrophoretic particles in the closed cell being  
changed according to a voltage between the first and second electrodes to effect display,

wherein the first electrode has an area substantially equal to or larger than an area of the second electrode, and

~~wherein the device further comprises~~ means for successively applying between the first and second electrodes a reset voltage and a writing voltage which have an identical amplitude and have polarities opposite to each other.

11. (Original) A device according to Claim 10, wherein the reset voltage has a polarity for distributing the electrophoretic particles on the first electrode.